

CURRENT 2.0 Ampere
VOLTAGE RANG 50 to 1000 Volts

RS201 THRU RS207

Features

- This series is SGS listed under the Recognized Component Index, file number SZXEC1902259902
- Ideal for printed circuit board mounting
- The plastic material used carries Underwriters Laboratory flammability recognition 94V-0
- Built-in printed circuit board stand-offs
- High case dielectric strength
- High temperature soldering guaranteed 265°C/10 seconds at 5 lbs (2.3kg) tension


Mechanical Data

Case: Reliable low cost construction utilizing molded plastic technique

Terminals: Plated leads solderable per MIL-STD-202, Method 208

Mounting Position: Any

Weight: 0.065 ounce, 2.2 grams (approx)



Dimensions in millimeters(1mm = 0.0394")

Maximum Ratings & Thermal Characteristics

Rating at 25°C ambient temperature unless otherwise specified, Resistive or Inductive load, 60 Hz.
For Capacitive load derate current by 20%.

Parameter	Symbol	RS 201	RS 202	RS 203	RS 204	RS 205	RS 206	RS 207	unit
Maximum repetitive peak reverse voltage	VRRM	50	100	200	400	600	800	1000	V
Maximum RMS bridge input voltage	VRMS	35	70	140	280	420	560	700	V
Maximum DC blocking voltage	VDC	50	100	200	400	600	800	1000	V
Maximum average forward rectified output current at TA=50°C	IF(AV)								A
Peak forward surge current single sine-wave superimposed on rated load (JEDEC Method)	IFSM								A
Rating for fusing (t<8.3ms)	I ² t								A ² sec
Typical thermal resistance per element(1)	ReJA								°C / W
Typical junction capacitance per element(2)	C _j								pF
Operating junction and storage temperature range	T _j , T _{STG}						-55 to + 150		°C

Electrical Characteristics

Rating at 25°C ambient temperature unless otherwise specified. Resistive or Inductive load, 60Hz.
For Capacitive load derate by 20 %.

Parameter	Symbol	RS 201	RS 202	RS 203	RS 204	RS 205	RS 206	RS 207	Unit
Maximum instantaneous forward voltage drop per leg at 1.0A	VF				1.1				V
Maximum DC reverse current at rated TA =25°C DC blocking voltage per element TA =125°C	IR				10				μA

Notes: (1)Thermal resistance from Junction to Ambert on P.C.board mounting.

(2)Measured at 2.0MHz and applied reverse voltage of 4.0 volts.

CURRENT 2.0 Ampere
VOLTAGE RANG 50 to 1000 Volts

RS201 THRU RS207

Rating and Characteristic Curves (TA=25°C Unless otherwise noted)

Fig. 1 Derating Curve for Output Rectified Current




Fig. 3 Typical Instantaneous Forward Characteristics




Fig. 2 Maximum Non-repetitive Peak Forward Surge Current




Fig. 4 Typical Reverse Characteristics




Fig. 5 Typical Junction Capacitance

